

Liwal Smart IP Phones Series

LA2-G300

The smart and simple enterprise IP Phone with user friendly interface and intelligent LCD at a competitive price.

Offering POE support, two Ethernet Ports, High Definition voice, full-duplex speakerphone and much more. Fully compatible with several IP PBX systems that supports SIP.



SPECIFICATIONS

LCD Display	128x48 dot-matrix backlit LCD
Lines	2 SIP Lines
HD Audio	HD Microphone and HD Speaker
Network Interfaces	Dual 10/100 Mbps Ethernet Ports with POE and bridged port for PC bypass, QoS, VLAN
Protocols	SIP 2.0 over UDP/TCP/TLS, RTP/RTCP/SRTP, STUN, DHCP, PPPoE, 802.1x, L2TP (Basic Unencrypted), OpenVPN, SNTP, FTP/TFTP, HTTP/HTTPS, TR069, Auto-Provisioning, Liwal Web GUI Management Portal
Codec	Narrowband G.711 μ/a , G.723.1, G726-32, G.729 A/B and Wide-band G.722 In-band and Out-of-Band DTMF Relay RFC2833, SIP INFO
Keys	31 keys Keypad including 4 Soft-keys, 7 Function keys, 4 Navigation keys, 1 Ok key, 12 Standard Phone Digits keys, 2 Volume Control keys, Up/Down, 1 Hands-free key
Headset/Hands-free	Handset, Hands-free (EHS supporting Plantronics headsets), RJ9 Headset Jack
Form Factor	Desktop and Wall Mountable with Desktop Stand
Call Features	Call out/answer/reject/hold/resume/waiting, transfer (Attended/Unattended), Forwarding (Always/Busy/No Answer), Mute/Unmute (mic), Intercom, Caller ID, Speed Dial, Anonymous Call (Hide Caller ID), Parking/Pick-up (depending on server), Redial/Auto-Redial, Do-Not-Disturb, Auto-Answering, 3-way conferencing, Voice Message (on server)
Phone Features	Phonebook (up to 500 entries), Remote Phonebook (XML/LDAP), Call log (100 entries), Black/White List Call Filtering, Voice Message Waiting Indication (VMWI), Programmable Soft keys, Network Time Synchronization, Action URL/Active URI
Security	User and Administrator level access control
Power	Universal Power Adapter 100-240VAC 50-60Hz, DC Power Input 5V 600mA
Temperature/Humidity	Operation Temperature: 0~40°C, Operation Humidity: 10~65%
Package	LA2-G300 Phone, Handset, Cord, Base Stand, Power Adapter, Ethernet Cable, Quick Installation Guide
Compliance	CE, FCC and RoHS
Physical	Dimensions: 260 x 255 x 62 mm (L x W x H), Phone Weight: 0.66 Kg; Box Weight: 0.86kg, Phone Color: Black, Environmental friendly box